

F48 Module

Features

- Vandal Resistant—Tamper Proof screws
- Suits 48.3mm x 2mm wall tube
- Lux Variable— See Lux table pg2
- Dimmable, On/Off or Dali lighting controls
- Easy Installation and Maintenance
- Parallel connection meaning if one module goes the others stay on
- Clear or Diffused Lens
- Asymmetric or Symmetric light flow
- 5 year Warranty



Wembley Park Blvd, London

Lighting Specs

Module Dimensions	140.0mm x 22.0mm
High Output + Emergency PCB	5 Watt with Emergency 0.29W
Operation Voltage	Stabilised 24V DC \pm 5%
Colour Temperature	Warm White 2700k—3000k, Neutral White 4000k
CRI	86
Material	Polycarbonate / Lumaax® & Antimicrobial
Fixings	Mechanical Fixing. M3 Bolts (Stainless Steel 316)
Maximum Module Qty.	30 + per driver
Luminaire Lumens (Clear Lens)	430
Lumens per Circuit Watt	86
Emergency Circuit Luminaire Lumens	108
Emergency Circuit Lumens per Circuit Watt	13.5
Additional Options	Emergency Feature / 3hr Battery Backup
Quality	British Made, CE Marking, Full Traceability, IP66, IK10





Limehouse Railway Station, London

Typical Lux Chart

Below Example of a F48 Module in a 4m area. To achieve higher Lux levels will depend on spacings. FULL PHOTOMETRIC DATA available on request

