

Spot Module

Features

- Vandal Resistant
- Suits 48.3mm x 2mm wall tube
- Lux Variable— See Lux table pg2
- Dimmable, On/Off or Dali lighting controls
- Easy Installation and Maintenance
- Clear Lens
- Asymmetric or Symmetric light flow
- 5 year Warranty



Jellicoe Gardens, London

Lighting Specs

Module Dimensions	28mm dia
High Output	2.5 Watt
Operation Voltage	Stabilised 24V DC \pm 5%
Colour Temperature	Warm White 2700k—3000k, Neutral White 4000k
CRI (Color rendering index)	85
Material	Polycarbonate Lens with Aluminium Thermal Core
Fixings	Simple push fit
Maximum Module Qty.	40 + per driver
Luminaire Lumens (Clear Lens)	65
Lumens per Circuit Watt	26
Ambient Temperature	25°C
Additional Options	Emergency Feature / 3hr Battery Backup
Quality	British Made, CE Marking, Full Traceability, IP66, IK10





Chobham Bridge, Surrey

Typical Lux Chart

Below Example of a Spot Module in a 5m area. To achieve higher Lux levels will depend on spacings. FULL PHOTOMETRIC DATA available on request

Mounting height: 900mm
 Tilt angle: 0.0°
 Swivel angle: 0.0°
 Orientation: 0.0°
 Light loss factor: 1.0

